

# SAFETY DATA SHEET

CLEAN RANGE 195-50-041 LABEL REMOVER 200ML WITH BRUSH

Page 1

Issued: 02/11/2004

Revision No: 1

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** CLEAN RANGE 195-50-041 LABEL REMOVER 200ML WITH BRUSH

**Product code:** 195-50-041 (21-034)

**Company name:** Durable UK Ltd

10 Nimrod Way

Wimborne

Dorset

BH21 7SH

Tel: 01202 897071

Fax: 01202 873381

Emergency tel: 01305 213770

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** BUTANE 10-30%

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

- LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),

HYDROTREATED LIGHT 30-50%

EINECS: 265-151-9 CAS: 64742-49-0

[F+] R12; [Xi] R38; [N] R51/53; [Xn] R65

## 3. HAZARDS IDENTIFICATION

**Main hazards:** Extremely flammable.

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

**SAFETY DATA SHEET**

CLEAN RANGE 195-50-041 LABEL REMOVER 200ML WITH BRUSH

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Keep away from direct sunlight.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** BUTANE  
WEL (8 hr exposure limit): 1450 mg/m<sup>3</sup> WEL (15 min exposure limit): 1810 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Solubility in water:** Insoluble

**Flash point°C:** <0

**Autoflammability°C:** 200

**Relative density:** <1

**SAFETY DATA SHEET**

CLEAN RANGE 195-50-041 LABEL REMOVER 200ML WITH BRUSH

**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat. Direct sunlight. Hot surfaces. Sources of ignition. Flames.**Materials to avoid:** Strong oxidising agents. Strong acids.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Chronic toxicity:** Danger of serious damage to health by prolonged exposure if swallowed. Danger of serious damage to health by prolonged exposure in contact with skin. Danger of serious damage to health by prolonged exposure through inhalation.**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Persistence and degradability:** No data available.**Bioaccumulative potential:** No data available.**Other adverse effects:** No data available.**13. DISPOSAL CONSIDERATIONS****NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1950**ADR Class:** 2**Classification code:** 5F**Shipping name:** AEROSOLS**Labelling:** 2.1**IMDG / IMO****UN no:** 1950**Class:** 2**EmS:** F-D,S-U**Marine pollutant:** .**Labelling:** 2.1**IATA / ICAO****UN no:** 1950**Class:** 2**Labelling:** 2.1

## SAFETY DATA SHEET

CLEAN RANGE 195-50-041 LABEL REMOVER 200ML WITH BRUSH

### 15. REGULATORY INFORMATION

**Hazard symbols:** Extremely flammable.



**Risk phrases:** R12: Extremely flammable.

**Safety phrases:** S16: Keep away from sources of ignition - No smoking.

S2: Keep out of the reach of children.

S51: Use only in well-ventilated areas.

S23: Do not breathe vapour.

S46: If swallowed, seek medical advice immediately and show this container or label.

**Precautionary phrases:** Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

### 16. OTHER INFORMATION

**Risk phrases used in s.2:** R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

